



3511 3 XX A M S XX B N A X

No. of Pins
NPin
N=30, 48,
96

Contact Type
M=Male

Contact	Plating
G0:Gold	Flash
S0:Gold	Flash/Tin
S1:3U"	Gold/Tin
S2:5U"	Gold/Tin
S3:10U"	Gold/Tin
S4:15U"	Gold/Tin
S5:30U"	Gold/Tin

Contact Material
B=Brass

Stream	Code
--------	------

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)

Dimension antitheses list	
ITEM	A
Standard	4.00

				OPERATION		DRAW	Jelly Feng	2023.03.29	SCALE	FIT	JILN[®] 深圳市锦凌电子有限公司 SHENZHEN JINLING ELECTRONICS CO.,LTD Tel: 86-755-27483253 Fax: 86-755-2997-5588	
				X.X	±0.30				UNIT	mm		
				X.XX	±0.20	CHECK			SIZE	A4		
				X.XXX	±0.10		SHEET	1/1	PART NO.	35113XXAMSXXBNAX		
A0	2023.03.29	NEW DRAWING		Angle	± 3°	APPROVE			PROJ.		TITLE:	欧式插座 公座 180度 3xNPin 成品系列图
REV	DATE	MODIFICATION DESCRIPTION		CHANGE	DIM TOL							

JILN® 深圳市锦凌电子有限公司
SHENZHEN JINLING ELECTRONICS CO.,LTD
Tel: 86-755-27483253 Fax: 86-755-2997-5588

PART NO.

35113XAMSXXBNAX

TITLE:

欧式插座 公座 180度 3xNPin 成品系列图