



SPECIFICATIONS

Current Rating:1.0AMP

Contact Resistance:10mΩ Max

Dielectric Strength:Min 1000V RMS

Operation Temperature:-40℃ to +105℃




Contact Material:Brass

Contact Plating:Au Over Ni

Insulator Material:Polyester(UL94V-0)

Standard: PPS

Max.Processing Temp: 260℃±5℃ For 5~10 Second



Ordering Information


3614 22 1 XX S XX 081 0X

No.of
Pins
NPIN
N=02~50

Contact Plating
G1:1U" Gold
G2:1.5U" Gold
G3:2U" Gold
G4:3U" Gold
G5:5U" Gold
S0:Gold Flash/Tin
SN:Tin

Pin Length
081=8.1mm

Serial code



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

				OPERATION		DRAW	Jelly Feng	2023.07.11	SCALE	FIT	JILN® 深圳市锦凌电子有限公司 SHENZHEN JINLING ELECTRONICS CO.,LTD Tel: 86-755-27483253 Fax: 86-755-2997-5588	
				X.X	±0.30				UNIT	mm		
				X.XX	±0.20	CHECK			SIZE	A4		
				X.XXX	±0.10				SHEET	1/1	PART NO.	3614221XXSXX081XX
A0	2023.07.11	NEW DRAWING			Angle	APPROVE			PROJ.		TITLE:	1.27x2.2 单排双头针 L=8.1针尖0.41 正装
REV	DATE	MODIFICATION DESCRIPTION		CHANGE	DIM TOL							