



SPECIFICATIONS

Rated Current:1.0AMP

Contact Resistance:20mΩ Max

Withstand Voltage:500V AC/DC

Insulation Resistance:1000MΩ Min

Operation Temperature:-40°C to +105°C

Contact Material:Brass

Contact Plating:Au Over Ni





Insulator Material:Polyester(UL94V-0)

Resistance To Soldering Heat:

245°C±5°C, 10s(PBT insulator)

260°C±5°C, 10s(PA6T&PA9T&LCP insulator)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Ordering Information

14XX 11 XX X N XX R XXX X 0X

High.of
Plastic
10=H1.0mm
15=H1.5mm
16=H1.6mm
17=H1.7mm
20=H2.0mm
25=H2.5mm
30=H3.0mm

No.of
Pins
Per Row
02~50P

Insulator Material
Option
A=BK-PBT
C=BK-PA6T
E=BK-PA9T
F=BK-LCP

Contact Plating
G0:Gold Flash
G1:1u" Gold
G2:1.5u" Gold
G3:2u" Gold
G4:3u" Gold
G5:5u" Gold
G6:10u" Gold
G7:15u" Gold
G8:30u" Gold
S0:Gold Flash/Tin
SN:Tin

Pin Length

Packing
O=PE Bag
A=Tray
T=Tube
P=Tube+Cap
R=Reel+Cap
M=Reel+Mylar

Dimension antitheses list

	H	1.0	1.5	1.6	1.7	2.0	2.5	3.0
W	2.0	2.5	2.0	2.5	2.5	2.5	2.5	2.5

Dimension antitheses list

ITEM	PA	PB	PC
Alternate	XXX	XXX	XXX

OPERATION

DRAW

RICH LIN

23.06.10

SCALE

FIT

X.X

±0.30

CHECK

X.XX

±0.20

X.XXX

±0.10

Angle

±3°

DIM

TOL

APPROVE

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

1/1

JILN® 深圳市锦凌电子有限公司
SHENZHEN JINLING ELECTRONICS CO.,LTD

Tel: 86-755-27483253 Fax: 86-755-2997-5992

PART NO.

14XX11XXXXXXRXXXX0X

TITLE:

1.27mm Pin Header 90°正弯

High.of
Plastic
10=H1.0mm
15=H1.5mm
16=H1.6mm
17=H1.7mm
20=H2.0mm
25=H2.5mm
30=H3.0mm

No.of
Pins
Per Row
02~50P

Insulator Material
Option
A=BK-PBT
C=BK-PA6T
E=BK-PA9T
F=BK-LCP

Contact Plating
G0:Gold Flash
G1:1u" Gold
G2:1.5u" Gold
G3:2u" Gold
G4:3u" Gold
G5:5u" Gold
G6:10u" Gold
G7:15u" Gold
G8:30u" Gold
S0:Gold Flash/Tin
SN:Tin

Pin Length

Packing
O=PE Bag
A=Tray
T=Tube
P=Tube+Cap
R=Reel+Cap
M=Reel+Mylar